

# Aperture Array Developments at ASTRON

Stefan J. Wijnholds  
e-mail: [wijnholds@astron.nl](mailto:wijnholds@astron.nl)

Phased Array Workshop  
Provo (Utah), 3 May 2010

## **Main aperture array projects**

- LOFAR
- EMBRACE

## **Concept design and subsystem studies**

- OLFAR
- Path to the SKA

# LOFAR – the **L**ow **F**requency **A**rray

M. de Vos, A.W. Gunst and R. Nijboer, Proc. IEEE, 2009

ASTRON

Phased array radio telescope consisting of

- 36+ Dutch stations with
  - 96 Low Band Antennas (LBA, 10 – 90 MHz)
  - 48 High Band Antenna tiles (HBA, 110 – 250 MHz)
    - 4x4 array -> total 768 HBAs / station
- 10+ international stations with 96 LBAs and 96 HBA tiles

Total:

- > 4400 LBAs
- > 43000 HBAs


- 29 stations with CEP connection
- 22 stations validated
- Station calibration tables being produced
- Many “busy weeks”: focused pipeline efforts
  - Standard imaging pipeline
  - Pulsar pipeline
  - Transient detection pipeline
- **LOFAR opening: 12 June 2010**

# LOFAR – Pulsar detection

Tom Hassall (PWG), AJDI 19 March 2010

Tom Hassall (PWG), AJDI 22 December 2009

ASTRON




# LOFAR – ITS ('04) vs. CS10 ('08) image

S.J. Wijnholds, URSI GA, 2005

S.J. Wijnholds, Ph.D. Thesis, 2010

ASTRON





# LOFAR – Beat NEWSTAR Project

Oleg Smirnov, SKA2010, 22-25 March 2010

ASTRON

- Goal: beat DR on 3C147 obtained by De Bruyn ( $2 \cdot 10^6$ )
- Main challenge: direction dependent effects (DDEs)



# Electronic Multi-Beam Radio Astronomy Concept

ASTRON

## EMBRACE-WSRT

- 144 single pol. tiles
- A-beam: 144 signal paths
- B-beam: 36 signal paths
- 72 tiles installed
- 192-input LOFAR backend

## EMBRACE Nancy

- 72 single pol. tiles
- 20 signal paths per beam



# EMBRACE – Backend

ASTRON


**180 CDCs (LO dist.)**

**192 RCUs**

- 110-190 MHz band
- 12 bit 200 MHz ADCs

**digital processing**

- 195 kHz subbands
- autocorrelations
- visibilities



# EMBRACE – Solar fringes

S.J. Wijnholds et al., SKADS conference, 4-6 November 2009

G.W. Kant et al., IEEE TrAP, in revision, 2010


ASTRON

## Interferometric measurement with 10 tiles

- two E-W ULAs
- frequency: 1179 MHz
- integration: 10 s
- bandwidth: 195 kHz

### Initial performance est.

- $A/T = 4.7 \cdot 10^{-3}$  (to sun)
- $T_{\text{sys}} = 103\text{-}117$  K (to zenith)



# EMBRACE – Redundancy



S.J. Wijnholds et al., SKADS Conference, 4-6 November 2010

P. Noorishad et al., SKADS Conference, 4-6 November 2010

ASTRON

## Redundant baselines produce redundant visibilities

Useful for calibration (under study by Parisa Noorishad)




# EMBRACE – 40 dB DR Afristar image

S.J. Wijnholds (EMBRACE team), AJDI, 26 January 2010

G.W. Kant et al., IEEE TrAP, in revision, 2010

ASTRON

Measured (left) and simulated (right) array factor



## Concept design study

**Goal:** low (< 10 MHz) frequency array in space

## Concept

- Antennas on formation flying micro-satellite
- One mother ship with central processing and downlink
- Distributed signal processing

**Partners:** Delft University of Technology, Twente University, ALTRAN, Astrium, Radboud University Nijmegen

## Aperture Array Verification Program (AAVP)

- Verification of EMBRACE
- Design improvement (lower  $T_{\text{sys}}$ , mass production)

## Other SKA studies (implicit and explicit)

- Virtual observatory: experience LOFAR and WSRT
- Calibration and imaging research
- Uniboard: generic digital signal processing board
- Photonic research: data transport, beam forming